



L'Hygiène Active de l'air et des surfaces par micro diffusion sèche

## ECOMATIC




### DESCRIPTION et AVANTAGES DU DIFFUSEUR

ECOMATIC est un diffuseur entièrement programmable pour un traitement efficace des volumes et des surfaces, hors présence humaine ou manuellement avec l'utilisation d'équipements de protection individuelle selon la Directive 89/686/CEE (voir fiche de données de sécurité).

Il permet ainsi la mise en place de protocoles de traitements périodiques et systématiques, que ce soit dans la lutte contre l'aérobiocontamination, la désinfection (**selon la norme NF T 72-281 en mode dispersât dirigé**), la destruction des odeurs ou encore la désinsectisation.



CARACTERISTIQUES	
Puissance :	120 W
Pression de sortie :	3,5 bars
Type de carrosserie :	Portative
Matière carrosserie :	Aluminium peint
Longueur hors tout :	26,5 cm
Largeur hors tout :	23 cm
Hauteur hors tout :	36 cm
Poids à vide / Poids emballé :	6,73 kg / 7,65 kg
Alimentation :	230 Vac
Réservoir :	Bidon amovible de 2L
Buse Delrin & injecteur titane – Système de purge automatique du circuit de liquide en fin de diffusion.	



### Ce diffuseur vous propose 3 différentes possibilités d'utilisation :

1. Utilisation manuelle.
2. Programmation d'un temps de diffusion avec démarrage immédiat.
3. Programmation en automatisme intégral.

Les diffuseurs HYGIASEPT® sont garantis 1 an. - Se reporter aux protocoles HygiaSept pour les temps de diffusion.

Seuls les produits de la gamme Hygiaseptyl® doivent être utilisés. Toute utilisation de liquides autres que ceux préconisés par HYGIASEPT® entraînent l'annulation de la garantie. Nous n'engageons pas notre responsabilité en cas d'utilisation non prévue de la présente notice.



Active Hygiene of air and surfaces by dry micro diffusion.

## ECOMATIC




### DESCRIPTION & ADVANTAGES OF THE DIFFUSER.

ECOMATIC is an entirely programmable diffuser which enables an efficient treatment of volumes and surfaces without human or animal presence or manually using personal protection equipment as per Directive 89/686/EEC (see safety data sheet).

With ECOMATIC, it is easy to implement periodical and routine treatment protocols to fight against aerobiocontamination, to disinfect (**according to NF T 72-281 with directed “dispersat” method**), to destroy odours or insects.



SPECIFICATIONS	
Power :	120 W
Outlet pressure (air) :	3,5 bars
Flexible length :	1,20 m
Bodywork type :	Portative
Bodywork material :	Painted Aluminium
Overall length :	26,5 cm
Overall width :	23 cm
Overall height :	36 cm
Weight empty / Overall Weight :	6,73 kg / 7,65 kg
Power supply :	230 Vac
Replacement Container :	2 litres container
Delrin nozzle and titanium injector – Liquid circuit automatic valve system at the end of each diffusion.	



**This diffuser offers 3 different possibilities :**

1. Manual use.
2. Programming spraying time with an immediate start.
3. Integrally automatic programming.

**HYGIASEPT® diffusers are guaranteed for one year.**

See Hygiasept protocols for spraying time estimation.

The use of products outside the Hygiaseptyl® range are not recommended with this diffuser and if used, we take no responsibility.